This listing of claims will replace all prior versions and listings of claims in the

application:

1. (Currently amended) An additive composition for a transmission oil comprising:

(a) an oil dispersion of a hydrated alkali metal potassium borate; and

(b) an oil dispersion of hexagon boron nitride;

wherein the weight ratio of the hydrated alkali-metal potassium borate to the

hexagonal boron nitride is in the range of about 95:5 2.1:1.0 to about 5:95 8.4:1.0.

2. (Cancelled)

3. (Cancelled).

4. (Currently amended) The additive composition according to Claim 3 1, wherein the

hydrated alkali metal potassium borate is hydrated potassium triborate.

5. (Currently amended) The additive composition according to Claim 1, wherein the oil

dispersion of hydrated alkali metal potassium borate contains a hydrated alkali metal

potassium borate, a dispersant and an oil of lubricating viscosity.

6. (Currently amended) The additive composition according to Claim 5, wherein the oil

dispersion of hydrated alkali-metal potassium borate contains about 10 to about 75

-2-

Application No.: 10/624,240 Filing Date: July 22, 2003

Attorney Docket No. T-6119

weight percent of the hydrated alkali metal potassium borate, based on the total weight of the oil dispersion.

- 7. (Currently amended) The additive composition according to Claim 5, wherein the oil dispersion of hydrated alkali metal potassium borate contains about 2 to about 40 weight percent of the dispersant, based on the total weight of the oil dispersion.
- (Currently amended) The additive composition according to Claim 5, wherein the oil dispersion of hydrated alkali-metal potassium borate further contains a detergent.
- 9. (Currently amended) The additive composition according to Claim 8, wherein the oil dispersion of hydrated alkali-metal potassium borate contains about 0.2 to about 10 weight percent of the detergent, based on the total weight of the oil dispersion.
- 10. (Currently amended) The additive composition according to Claim 1, wherein the oil dispersion of hydrated alkali metal potassium borate is present in the additive composition in the range of about 10 to about 90 weight percent, based on the total weight of the additive composition.
- 11. (Original) The additive composition according to Claim 1, wherein the hexagonal boron nitride has a particle size distribution wherein 90% or greater of the particles are less than about 0.5 microns.
- 12. (Original) The additive composition according to Claim 1, wherein the oil dispersion of hexagonal boron nitride contains an oil of lubricating viscosity and about 1 to

Application No.: 10/624,240 Filing Date: July 22, 2003

Attorney Docket No. T-6119

about 50 weight percent of hexagonal boron nitride, based on the total weight of the

oil dispersion.

13. (Original) The additive composition according to Claim 12, wherein the oil dispersion

of hexagonal boron nitride further contains a surfactant as a stabilizer.

14. (Original) The additive composition according to Claim 1, wherein the oil dispersion

of hexagonal boron nitride is present in the additive composition in the range of about

10 to about 90 weight percent, based on the total weight of the additive composition.

15. (Currently amended) A lubricating oil composition comprising a major amount of a

transmission oil of lubricating viscosity and about 1 to about 20 weight percent of an

additive composition, based on the total weight of the lubricating oil composition,

comprising:

(a) an oil dispersion on a hydrated alkali-metal potassium borate; and

(b) an oil dispersion of hexagonal boron nitride:

wherein the weight ratio of the hydrated alkali-metal potassium borate to the

hexagonal boron nitride is in the range of about 95:5 2.1:1.0 to about 5:95 8.4:1.0.

16. (Cancelled).

(Original) The lubricating oil composition according to Claim 15, wherein the

transmission oil is a manual transmission gear oil.

-4-